





WENZHOU KAIXU AUTOMOBILE FITTING CO.,LTD

DIN6799(KX-DBK 1.2-24.0)(spring E-ring E型开口挡圈)



轴径 d ₂		d ₁		外径 d ₄ max	口宽 a		厚度 S		C ₂	槽宽m	重量 公斤/千只 ≈
基本尺寸	极限偏差 h11	最小 min	最大 max		基本尺寸	极限偏差	基本尺寸	极限偏差	基本尺寸	基本尺寸	
1.2	-0.060	1.4	2.0	2.90	1.01	±0.04	0.30	±0.02	3.0	0.34	0.009
1.5		2.0	2.5	3.90	1.28		0.40		4.0	0.44	0.021
1.9		2.5	3.0	4.40	1.61		0.50		4.5	0.54	0.040
2.3		3.0	4.0	5.90	1.94		0.60		6.0	0.64	0.069
3.2	-0.075	4.0	5.0	6.90	2.70	±0.048	0.70		7.0		0.088
4.0		5.0	7.0	8.85	3.34				9.0	0.74	0.158
5.0		6.0	8.0	10.85	4.11				11.0		0.236
6.0		7.0	9.0	11.80	5.26				12.0		0.255
7.0	-0.090	8.0	11.0	13.80	5.84	±0.058	0.90	±0.03	14.0	0.94	0.474
8.0		9.0	12.0	15.75	6.52		1.00		16.0	1.05	0.660
9.0		10.0	14.0	18.20	7.63		1.10		18.5	1.15	1.000
10.0		11.0	15.0	19.70	8.32		1.20		20.0	1.25	1.120
12.0	-0.110	13.0	18.0	22.70	10.45	±0.070	1.30		23.0	1.35	1.770
15.0		16.0	24.0	28.70	12.61		1.50		29.0	1.55	3.370
19.0	-0.130	20.0	31.0	36.50	15.92	±0.084	1.75		37.0	1.80	6.420
24.0		25.0	38.0	43.50	21.88		2.00		44.0	2.05	8.550