





# WENZHOU KAI XU AUTOMOBILE FITTING CO., LTD

(KX-VMK 10-100) (spring V-ring for bore 孔用V型弹性挡圈)



公称直径 d1	外径 d3		厚度 S		槽直径 d2		槽宽 m min	孔径 d5 min	头宽 a max	尾宽 b ≈	重量 Kg/1000 ≈
	基本尺寸	极限偏差	基本尺寸	极限偏差	基本尺寸	极限偏差					
10	10.90	+0.42 -0.13	0.60	-0.05	10.50	+0.11	0.70	0.90		1.50	0.15
12	13.10		12.60		1.80					0.25	
15	16.10		15.70		2.00		0.41				
16	17.30		16.80		2.10		0.53				
17	18.30		17.80		2.10		0.58				
18	19.50		19.00		2.20		0.62				
19	20.50		20.00		2.30		0.66				
20	21.50		21.00		2.30		0.80				
21	22.50		22.00		2.40		0.81				
22	23.50		23.00		2.40		0.83				
24	25.90	+0.42 -0.21	1.20	-0.06	25.20	+0.21	1.30	1.50	2.80	1.30	
25	26.90				26.20				3.00	1.40	
26	27.90				27.20				3.00	1.50	
27	29.10				28.40				3.10	1.53	
28	30.10				29.40				3.10	1.80	
30	32.10				31.40				3.20	2.03	
32	34.40				33.70				3.30	2.05	
33	35.50				34.70				3.30	2.35	
35	37.80				37.00				3.40	3.20	
36	38.80				38.00				3.60	3.23	
38	40.80	40.00	3.80	3.68							
40	43.50	+0.90 -0.39	1.75		42.50	+0.25	1.60	1.70	4.20	4.75	
42	45.50				44.50				4.20	5.20	
45	48.50				47.50				4.70	6.00	
47	50.50				49.50				4.70	6.50	
48	51.50				50.50				4.70	7.00	
50	54.20				53.00				5.20	8.50	
52	56.20				55.00				5.20	9.00	
55	59.20				58.00				5.20	10.00	
57	61.20				60.00				5.20	10.25	
58	62.20				61.00				5.20	10.50	
60	64.20	+1.10 -0.46	2.00	-0.07	63.00	+0.30	2.15	2.50	11.25	11.25	
62	66.20				65.00				11.75	11.75	
65	69.20				68.00				16.25	16.25	
67	71.50				70.00				17.30	17.30	
68	72.50				71.00				17.75	17.75	
72	76.50				75.00				19.60	19.60	
80	85.50				83.50				22.90	22.90	
85	90.50				88.50				30.00	30.00	
90	95.50				93.50				33.00	33.00	
95	#####				98.50				37.50	37.50	
100	105.5	103.50	41.90	41.90							